

Product Data Sheet

RF-194 RHINOZ Venetian Loft

PRODUCT DESCRIPTION

RHINOZ Venetian Loft is a highly polished contemporary and industrial style acrylic finish that comes in various color choices, specially formulated for no crack, chalk or no dust. The application gives an illusion of depth and texture and creates a unique personalized design on walls, columns and ceilings, for interior and exterior. It has good adhesion, strength, durability, and weather resistant property, and contains active biocides to resist growth of mold and mildew. It can be used over variety of common substrate materials such as concrete, masonry, plaster, fiber cement, gypsum board and etc.

PRODUCT ADVANTAGES

Easy to apply by trowel
 Various color choices
 Good adhesion
 Good weather resistance
 Antimicrobial
 No chalk, no dust, no crack
 Interior and exterior use
 Safe and environmentally friendly

TECHNICAL DATA

Base : Acrylic polymer
 Appearance : Viscous paste
 PH : 8.0 – 10.0
 Density : 1.3 – 1.5 g/cm
 Surface dry : 20 - 30 minutes (Depend on condition)
 Top coating/painting : 1 - 2 hours (Depend on condition)
 Dry to sand : 4 – 6 hours (Depend on condition)

PACKING DATA

4 kg	4 units/ carton	30 cartons/ 1 full pallet
20 kg	1 unit/ carton	36 carton/ 1 full pallet

COVERAGE

1.4 kg./sqm for 1 mm thickness (depend on texture)

TOOLS & EQUIPMENT

Brush, Trowel, Sanding paper

RECOMMENDED USES

Modern / Contemporary style of residence or building	
Exterior & Interior Wall	Restaurant & Café
Gallery Studio	Theme Park
Resort & Hotel	Architectural Landmark

RECOMMENDATION

- Store in dry place with 1-year shelf life in the original unopened packing, at the temperature under 50 °C.
- Do not mix the product with water, as the product is ready-to-use.
- Not recommend to use for exterior, on floor area, and on surface that is always in contact with water or moisture e.g. swimming pool, shower recess area, etc.
- In case the product is not yet finished up, close the package lid tightly.

APPLICATION PROCESS

1. Surfaces must be clean, dry, structurally sound and free from other materials that will have effect on adhesion
2. Apply 1 coat of RHINOZ Primer Bonding, then leave it dry for 15-30 minutes
3. Skim 1 coat of RHINOZ Bond Skim on the desired area, then leave it dry for 1-2 hours
4. Skim the 1st coat of RHINOZ Venetian Loft with trowel in a thin layer while adding thickness in some area to create pattern for the illusion of depth and texture. Leave it dry for about 1 hour
5. Apply the 2nd coat of RHINOZ Venetian Loft with trowel on to the whole area. Leave it for 10-20 minutes
6. Use trowel to touch up, polish, and smoothen the finish, and leave it dry completely for 4-6 hours
7. Sandpaper can be used for a smoother finish, wipe off the dust and chalk

TEXTURE & COLOR OPTIONS

RHINOZ Venetian Loft is a polished acrylic finish that provides extra smooth touch, able to create special design like marble pattern.

	VL-01		VL-02
	VL-03		VL-04
	VL-05		VL-06
	VL-07		VL-08
	VL-09		VL-10
	VL-11		VL-12
	VL-W		VL-BK
	Mixing colors (VL-W + VL-02 + VL-BK)		
	Mixing colors (VL-W + VL-09 + VL-10)		