



**BLUE LABEL CO.,LTD.**

48/58 Moo.1 Ekachai Road, Khok-Krabue, Amphur Muang, Samutsakhon, 74000 Thailand  
Tel : +66 3449 4774-5 Fax : +66 3449 4776 Website : www.bluelabelgroup.com

*Technical Data Sheet*

**RHINOZ – Innovation Special Products**

# **RHINOZ<sup>®</sup> RF-194**

## **RHINOZ Venetian Loft**

### **FEATURES**

- Easy to apply by trowel
- Various color choices
- Good adhesion
- Good weather resistance
- Antimicrobial
- No crack, no chalk, no dust
- Interior and exterior use
- Safe and environmentally friendly

### **DESCRIPTIONS**

RHINOZ Venetian Loft is a highly polished contemporary and industrial style acrylic finish that comes in various color choices, specially formulated for no crack, chalk or no dust. The application gives an illusion of depth and texture and creates a unique personalized design on walls, columns and ceilings, for interior and exterior. It has good adhesion, strength, durability, and weather resistant property, and contains active biocides to resist growth of mold and mildew. It can be used over variety of common substrate materials such as concrete, masonry, plaster, fiber cement, gypsum board and etc.

### **APPLICATION**

1. Surfaces must be clean, dry, structurally sound and free from other materials that will have effect on adhesion
2. Apply 1 coat of **RHINOZ Primer Bonding**, then leave it dry for 15-30 minutes
3. Skim 1 coat of **RHINOZ Bond Skim** on the desired area, then leave it dry for 1-2 hours
4. Skim the 1st coat of **RHINOZ Venetian Loft** with trowel in a thin layer while adding thickness in some area to create pattern for the illusion of depth and texture. Leave it dry for about 1 hour
5. Apply the 2nd coat of **RHINOZ Venetian Loft** with trowel on to the whole area. Leave it for 10-20 minutes
6. Use trowel to touch up, polish, and smoothen the finish, and leave it dry completely for 4-6 hours
7. Sandpaper can be used for a smoother finish, wipe off the dust and chalk

### **PACKING SIZE**

4 kg.      20 kg.

### **STORAGE**

Store in a dry place with shelf life 1 year in the original unopened packing

### **TECHNICAL DATA**

Base	:	Acrylic polymer	
Appearance	:	Colored viscous paste	
Colour	:	See color chart	
pH	:	8.0 - 10.0	
Density	:	1.3 - 1.5 g/cm <sup>3</sup>	
Dry to touch	:	20 - 30 minutes	( Depending on ambient conditions and thickness )
Dry to recoat	:	1 - 2 hours	( Depending on ambient conditions and thickness )
Dry to sand	:	4 - 6 hours	( Depending on ambient conditions and thickness )
Coverage	:	1.4 kg./ m <sup>2</sup> /1 mm.	