



BLUE LABEL CO.,LTD.

48/58 Moo.1 Ekachai Road, Khok-Krabue, Amphur Muang, Samutsakhon, 74000 Thailand
Tel : +66 3449 4774-5 Fax : +66 3449 4776 Website : www.bluelabelgroup.com

Technical Data Sheet

RHINOZ – Innovation Special Products

RHINOZ[®] RF-125

RHINOZ Multicolour

FEATURES

- Create a wide variety of patterns
- Easy to apply and low smell
- Durable
- Good adhesion
- Attractive and seamless
- Interior and exterior use
- Safe and environmentally friendly
- Antimicrobial

DESCRIPTIONS

RHINOZ Multicolour is a water-based spray applied seamless multicolour paint finishing. The product is designed to imitate natural granite stone and offers up to 12 choices of color. With easy application, the product can add luxury and elegant impression to the wall and furniture texture. It is durable and abrasion resistant, which minimizes maintenance costs. It contains active biocides to resist growth of mold and mildew on the paint film. It is ideal for walls, pillars, ceilings and other architectural structures, especially continuously occupied spaces. It can be used over variety of common substrate materials such as concrete, masonry, plaster, fiber cement, gypsum board, etc.

APPLICATION

1. Surfaces must be clean, dry, structurally sound, free from other materials that will have effect on adhesion.
2. Apply 1 coat of **RHINOZ Multicolour Basetone**, then leave it dry for 1 hour
3. Spray **RHINOZ Multicolour** by hopper gun
4. Leave to completely dried for 24 hours, apply **RHINOZ Acrylic Top (w)** or **RHINOZ Acrylic Top (s)**.

The Multicolor surface will be completely cured in 7 days.

PACKING SIZE

1 gallon 5 gallon

STORAGE

Store in a dry place with shelf life 1 year in the original unopened packing

TECHNICAL DATA

Base	:	Acrylic polymer	
Appearance	:	Colored viscous liquid	
Color	:	See color chart	
pH	:	8.0 - 10.0	
Density	:	1.0 - 1.2 g/cm ³	
Dry to touch	:	1 - 2 hours	(Depending on thickness and ambient conditions)
Hard dry	:	overnight	(Depending on thickness and ambient conditions)
Full cure time	:	7 days	(Depending on thickness and ambient conditions)
Coverage	:	10 - 15 m ² /gallon	(Depending on the texture)