



BLUE LABEL CO.,LTD.

48/58 Moo.1 Ekachai Road, Khok-Krabue, Amphur Muang, Samutsakhon, 74000 Thailand
Tel : +66 3449 4774-5 Fax : +66 3449 4776 Website : www.bluelabelgroup.com

Technical Data Sheet

RHINOZ – Innovation Special Products

RHINOZ[®] RF-242

RHINOZ Nano Lock

FEATURES

- Easy to use and low smell
- Good adhesion
- High opacity
- Long durability
- Good weather and moisture resistance
- Available of variety surfaces
- Both exterior and interior used
- Safe and environmentally friendly

DESCRIPTIONS

It is 100% acrylic water-based paint that provides superior protection and beauty for both exterior and interior. It can be used on masonry, fiber cement, wood, primed metal and etc. It gives smooth film, good adhesion, weathering resistance, moisture resistance, contains an antimicrobial additive to protect bacteria, fungi, yeasts and algae. It is environmentally friendly and contains no added lead and no added mercury. It can be applied to bare surfaces or previously painted surfaces.

APPLICATION

1. Surface must be dry, clean, free of dust, oil, grease and other contaminates that will effect to adhesion.
2. Stir **RHINOZ Nano Lock** thoroughly before and during application.
3. Apply 1-2 coats of **RHINOZ Nano Lock** by brush or roller, allow 1-2 hours dry time between coats.
4. Let it dry for 1-2 days before use and it shows high performance after 7 days.
5. Clean tools and equipment with water.

PACKING SIZE

1 Litre 4 Litre

STORAGE

Store in a dry place with shelf life 1 year in the original unopened packing.

TECHNICAL DATA

Base	:	Acrylic polymer	
Appearance	:	Coloured liquid	
Colour	:	See colour chart	
pH	:	8.0 - 10.0	
Density	:	1.1 - 1.3 g/cm ³	
Surface dry	:	20 - 30 minutes	(Depending on thickness and ambient conditions)
Re-coat time	:	1 - 2 hours	(Depending on thickness and ambient conditions)
Coverage	:	20 - 25 m ² /Litre/coat	(thickness 50 microns)