



**BLUE LABEL CO.,LTD.**

48/58 Moo.1 Ekachai Road, Khok-Krabue, Amphur Muang, Samutsakhon, 74000 Thailand  
Tel : +66 3449 4774-5 Fax : +66 3449 4776 Website : www.bluelabelgroup.com

*Technical Data Sheet*

**RHINOZ – Innovation Special Products**

# **RHINOZ<sup>®</sup> RF-134**

## **RHINOZ Hybrid Jointing Compound**

### **FEATURES**

- Easy to mix and apply
- Excellent adhesion to most surfaces
- Good mechanical strength and flexibility
- Non sag on vertical surfaces
- Durable and weather resistant
- Vibration and impact resistant
- Non shrinkage
- Non water absorption

### **DESCRIPTIONS**

It is a two component, joint sealing compound based on epoxy modified polyurethane. It is ideal for sealing joints, movement joints, expansion joints and repairing cracks. It is excellent adhesion to most surfaces such as concrete, masonry, precast, fiber concrete, wood and other construction materials. It is high strength, flexible, vibration and impact resistant. It is non-sag on vertical surfaces and non-shrinking due to their high-solids content. It is easy to mix and can be applied by using either a trowel or spatula.

### **APPLICATION**

1. Mix Part-A/B = 3/1 part by weight, mix thoroughly using either hand tools or low speed mixer 300-500 rpm.
2. Mixed until to be homogeneous and the mixed epoxy should be used within 60 minutes
3. For applications where joints are very deep, recommend to use backing rod prior to fill the jointing compound
4. Apply **RHINOZ Hybrid Jointing Compound** by trowel or spatula into the joints or the desired area
5. Allow a minimum of 24-48 hours setting time, before painting or applying a covering material
6. Clean tools and equipment with warm water or thinner before the products dries

### **PACKING SIZE**

1 kg./set

### **STORAGE**

Store in a dry place with shelf life 1 year in the original unopened packing

### **TECHNICAL DATA**

Base	:	(A) Epoxy modified	(B) Hardener
Appearance	:	(A) White viscous	(B) Black viscous
Mixing ratio	:	Part-A/B = 3/1 part by weight	
Pot life	:	60 minutes	
Setting time	:	24 - 48 hours	( Depending on ambient conditions and thickness )
Cure time	:	7 days	( Depending on ambient conditions and thickness )
Coverage	:	6 m./1 kg/set	( Dimension 1x1 cm. )