



BLUE LABEL CO.,LTD.

48/58 Moo.1 Ekachai Road, Khok-Krabue, Amphur Muang, Samutsakhon, 74000 Thailand
Tel : +66 3449 4774-5 Fax : +66 3449 4776 Website : www.bluelabelgroup.com

Technical Data Sheet

RHINOZ – Innovation Special Products

RHINOZ[®] RF-112

RHINOZ Stucco Flex

FEATURES

- High flexibility
- Good adhesion
- High strength and durability
- Antimicrobial
- Good weather resistance
- Cover cracks
- Interior and exterior use
- Safe and environmentally friendly

DESCRIPTIONS

RHINOZ Stucco Flex is 100% acrylic based, used as a decorative textured coating with unlimited unique finish as per your design. It is flexible and cover cracks well, suitable for wall and ceiling for exterior and interior application. It is applied easily using hopper gun, trowel, and paint roller. It contains active biocides to resist growth of mold and mildew, ensures long durability and weather resistant properties. It can be used over variety of common substrate materials, both new and old surfaces such as concrete, fiber cement, gypsum board, etc.

APPLICATION

1. Surfaces must be clean, dry, structurally sound and free from other materials that will effect to adhesion
2. Apply 1 coat of **RHINOZ Primer Bonding**, then leave it dry for 15-30 minutes. Not recommend to leave the surface too long after applied primer, as the surface might be collecting some dust.
3. Spray **RHINOZ Stucco Flex** with hopper gun to create texture. Roller or trowel also can be used for application and creating texture. Leave it dry for 15-20 minutes.
4. To flatten out the stucco surface for smoother look or soft-edged knock down texture, press a wet PVC roller over the stucco while it is not yet dried (optional).
5. Leave it to completely dry at least 24 hours or overnight before applying **RHINOZ Acrylic Top (W)** or **RHINOZ Acrylic Top (S)** or **RAY Decorative Paints**. The stucco surface will be completely cured in 7 days.

PACKING SIZE

5 kg. 25 kg.

STORAGE

Store in a dry place with shelf life 1 year in the original unopened packing

TECHNICAL DATA

Base	:	Acrylic polymer	
Appearance	:	Viscous paste	
Colour	:	See colour chart	
pH	:	9.0 - 11.0	
Density	:	1.5 - 1.7 g/cm ³	
Surface dry	:	15 - 20 minutes	(Depending on thickness and ambient conditions)
Top coating/painting	:	24 hours	(Depending on thickness and ambient conditions)
Full cure time	:	7 days	(Depending on thickness and ambient conditions)
Coverage	:	1.5 kg./m ² /1 mm.	(Depending on the texture)

DISCLAIMER : The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.