



BLUE LABEL CO.,LTD.

48/58 Moo.1 Ekachai Road, Khok-Krabue, Amphur Muang, Samutsakhon, 74000 Thailand
Tel : +66 3449 4774-5 Fax : +66 3449 4776 Website : www.bluelabelgroup.com

Technical Data Sheet

RHINOZ – Innovation Special Products

RHINOZ[®] RF-191

RHINOZ Metallic Loft

FEATURES

- Easy to apply by trowel
- Various color with pearl-like finish
- Good adhesion
- Good weather resistance
- Antimicrobial
- No crack, no chalk, no dust
- Interior and exterior use
- Safe and environmentally friendly

DESCRIPTIONS

RHINOZ Metallic Loft is a highly polished contemporary and industrial style acrylic finish that comes in various color choices with pearl-like finish, specially formulated for no crack, no chalk or no dust. The application gives an illusion of depth and texture and creates a unique personalized design on walls, columns and ceilings, for interior and exterior. It has good adhesion, strength, durability, and weather resistant property, and contains active biocides to resist growth of mold and mildew. It can be used over variety of common substrate materials such as concrete, masonry, plaster, fiber cement, gypsum board and etc.

APPLICATION

1. Surfaces must be clean, dry, structurally sound and free from other materials that will have effect on adhesion
2. Apply 1 coat of RHINOZ Primer Bonding, then leave it dry for 15-30 minutes
3. Skim 1 coat of RHINOZ Bond Skim on the desired area, then leave it dry for 1-2 hours
4. Skim the 1st coat of RHINOZ Metallic Loft with trowel in a thin layer while adding thickness in some area to create pattern for the illusion of depth and texture. Leave it dry for about 1 hour
5. Apply the 2nd coat of RHINOZ Metallic Loft with trowel on to the whole area. Leave it for 10-20 minutes
6. Use trowel to touch up, polish, and smoothen the finish, and leave it dry completely for 4-6 hours
7. Sandpaper can be used for a smoother finish, wipe off the dust and chalk

PACKING SIZE

4 kg. 20 kg.

STORAGE

Store in a dry place with shelf life 1 year in the original unopened packing

TECHNICAL DATA

Base	:	Acrylic polymer	
Appearance	:	Colored viscous paste	
Colour	:	See color chart	
pH	:	8.0 - 10.0	
Density	:	1.2 - 1.4 g/cm ³	Density
Dry to touch	:	20 - 30 minutes	(Depending on ambient conditions and thickness)
Dry to recoat	:	1 - 2 hours	(Depending on ambient conditions and thickness)
Dry to sand	:	4 - 6 hours	(Depending on ambient conditions and thickness)
Coverage	:	1.3 kg./ m ² /1 mm.	