

RHINOZ



nano Lock



RF-242

RHINOZ Nano Lock

NEW! Moisture resistant Nano Silicate paint One and only paint for damp area



RHINOZ nano Lock

The Paint of The Decade



Lock the paint molecule into the wall without peeling off



Lock away the efflorescence



15 years durability

Tested according to TIS 2312-2549



Lock the pigment to maintain its aesthetic



Lock away the fungi and algae



NANO LOCK TECHNOLOGY

New technology that combines nano molecules of pigment and nano silicate to enhance penetration into cement, adhere, and be one with the surface. No more problems of peeling off. Enhance strength with nano silicate and shield the wall and floor for its aesthetic to last 15 years without peeling off even in moist or damp area.



Weather Resistant

Long protect up to 15 years. Extra strength attained by deep penetration, shielding the surface from weathering. Moisture resistant and suitable for both interior and exterior. (Tested according to TIS 2312-2549)



High Flexibility

High flexibility. Reduce cracking, fracture, and chipping off.

(Tested according to ISO 1519)



High Adhesion

High adhesion due to penetration of pigment molecule into the wall. Eliminate problem of paint peeling off.



Fast Application

Reduce application steps. No primer needed. Can be applied right away on damp surface and 1 day after cement plastering. Can be painted over.



No Lead or Mercury

Manufactured with clean technology, odor free, no cancer-causing ingredient or lead or mercury. No leftover toxin. Safe for applicator and residents.



No Fungi and Bacteria

Clean and hygienic with special additive from TROY that has antimicrobial property to prohibit growth of fungi and bacteria throughout the product life.


(Tested according to ISO 22196)



RHINOZ nano Lock

NEW! Moisture resistant Nano Silicate paint One and only paint for damp area

With special properties of nano silicate and nano pigment that penetrate deeper than typical paints, the paint merge and lock into the surface, preventing the paint from peeling off even in moist or damp area such as wall base, wall, and fence. The paint can also camouflage cracks and pores and prevent from efflorescence. With high flexibility and adhesion, the paint reduces cracking. The application is fast and easy with no primer needed on either existing cement or fresh cement.





RF-242

RHINOZ nano Lock

Nano silicate paint, moisture resistant with no peeling, swelling, or efflorescence. Suitable for cement wall, floor, and roof in moist area like base wall, garden, and fence.

TECHNICAL DATA		
Base	: Nano Silicate Acrylic Polymer	
Film Appearance	: Sheen	
рН	: 8.0 - 10.0	
Colour	: 16 Colours (See colour chart)	
Recoat Time	: 1-2 Hours	
Cure Time	: 7 Days	
Scrub Resistance	: >15,000 (ASTM D2486)	
Bending Test	: Ø 2 mm (ISO 1519)	
Alkali Resistance	: Pass (TIS 285)	
Pull Off Adhesioที	: 5B 0% Peel Off (ASTM D3359)	
Unit Size	: 1 Litre and 4 Litre	
Coverage	: 20-25 sqm/lit/coat (at 100 mioron)	

Store in dry and clean place at the temperature under 50°C

APPLICATION

- 1. Surface must be dry, clean, free of dust, oil, grease and other contaminates that will effect to adhesion.
- 2. Stir RHINOZ Nano Lock thoroughly before and during application.
- 3. Apply 1-2 coats of RHINOZ Nano Lock by brush or roller, allow 1-2 hours dry time between coats.
- 4. Let it dry for 1-2 days before use and it shows high performance after 7 days.





Manufactured by:

BLUE LABEL Co.,Ltd.

48/58 Moo 1 Ekachai rd. Khok-krabue, Mueang,

Samutsakhon, 74000 THAILAND

Tel: (+66) 34-494-774 www.rhinozinternational.com

facebook RHINOZ International Q YOU Tibe bluelabel.innovation Q



Distributed by: